



## Fittings til metalslanger

### • SC-PC fitting

Metalfitting i forniklet messing.

#### Egenskaber og fordele

- Todelt fitting uden gevind
- Fungerer som låseenhed
- Giver glat gennemgang




HelaGuard SC-PC fitting.

|                         |                         |
|-------------------------|-------------------------|
| <b>MATERIALE</b>        | Forniklet messing (NPB) |
| <b>Driftstemperatur</b> | -100 °C til +300 °C     |

HF ✓

RoHS ✓



HelaGuard fittings, konnektor

| TYPE    | Nominel Ø | Min. hul størrelse (B) | L (L) | A/F krop (A/F1) | Enhed   | Farve      | EAN           | Bestillings-nr. |
|---------|-----------|------------------------|-------|-----------------|---------|------------|---------------|-----------------|
| SC10-PC | 10        | 5,6                    | 15,0  | 13              | 10 Stk. | Metal (ML) | 4031026306575 | 166-30500       |
| SC12-PC | 12        | 8,5                    | 15,5  | 17              | 10 Stk. | Metal (ML) | 4031026306582 | 166-30501       |
| SC16-PC | 16        | 11,5                   | 20,0  | 20              | 10 Stk. | Metal (ML) | 4031026306599 | 166-30502       |
| SC20-PC | 20        | 15,3                   | 16,5  | 24              | 10 Stk. | Metal (ML) | 4031026306605 | 166-30503       |
| SC25-PC | 25        | 19,1                   | 20,5  | 29              | 10 Stk. | Metal (ML) | 4031026306612 | 166-30504       |
| SC32-PC | 32        | 26,2                   | 23,5  | 38              | 2 Stk.  | Metal (ML) | 4031026306629 | 166-30505       |
| SC40-PC | 40        | 34,2                   | 24,8  | 48              | 2 Stk.  | Metal (ML) | 4031026306636 | 166-30506       |
| SC50-PC | 50        | 44,8                   | 30,0  | 58              | 1 Stk.  | Metal (ML) | 4031026306643 | 166-30507       |
| SC63-PC | 63        | 54,5                   | 33,5  | 70              | 1 Stk.  | Metal (ML) | 4031026306650 | 166-30508       |
| SC75-PC | 75        | 66,5                   | 42,0  | 84              | 1 Stk.  | Metal (ML) | 4031026306667 | 166-30509       |

Alle dimensioner i mm. Der tages forbehold for tekniske ændringer.  
Minimum ordre antal (MOQ) kan være forskellig fra emballageindhold.