



Fittings til metalslanger med plast coating

- PCS-PC fitting, IP54

Metalfitting i forniklet messing.

Egenskaber og fordele

- Hurtig montage
- Fastholder slangen optimalt
- Fungerer som en lås




HelaGuard SC-PC fitting.

MATERIALE	Forniklet messing (NPB)
Driftstemperatur	-100 °C til +300 °C

HF ✓

RoHS ✓



HelaGuard fitting, konnektor

TYPE	Nominal Ø	Min. hul størrelse (B)	L (L)	A/F krop (A/F1)	Enhed	Farve	EAN	Bestillings- nr.
PCS10-PC	10	5,6	15,0	13	10 Stk.	Metal (ML)	4031026307305	166-31200
PCS12-PC	12	8,5	15,5	17	10 Stk.	Metal (ML)	4031026307312	166-31201
PCS16-PC	16	11,5	20,0	20	10 Stk.	Metal (ML)	4031026307329	166-31202
PCS20-PC	20	15,3	16,5	24	10 Stk.	Metal (ML)	4031026307336	166-31203
PCS25-PC	25	19,1	20,5	29	10 Stk.	Metal (ML)	4031026307343	166-31204
PCS32-PC	32	26,2	23,5	38	2 Stk.	Metal (ML)	4031026307350	166-31205
PCS40-PC	40	34,2	24,8	48	2 Stk.	Metal (ML)	4031026307367	166-31206
PCS50-PC	50	44,8	30,0	58	1 Stk.	Metal (ML)	4031026307374	166-31207
PCS63-PC	63	54,5	33,5	70	1 Stk.	Metal (ML)	4031026307381	166-31208
PCS75-PC	75	66,5	42,0	84	1 Stk.	Metal (ML)	4031026307398	166-31209

Alle dimensioner i mm. Der tages forbehold for tekniske ændringer.
Minimum ordre antal (MOQ) kan være forskellig fra emballageindhold.