



HelaGuard tilbehør

- ALS låsemøtrik, galvaniseret stål

Sekskantet ALS låsemøtrik anvendes til at sikre fittings.




ALS låsemøtrik i galvaniseret stål.

MATERIALE	Galvaniseret stål (GS)
Driftstemperatur	-100 °C til +300 °C

HF ✓

RoHS ✓



HelaGuard låsemøtrik

TYPE	Møtrik str.	A/F møtrik (A/F3)	Modstående hjørner (A/C)	Tykkelse (T)	Enhed	Farve	EAN	Bestillings-nr.
ALS-M16	M16	24	27	3	10 Stk.	Metal (ML)	4031026309828	166-50119
ALS-M20	M20	25	28	3	10 Stk.	Metal (ML)	4031026309835	166-50120
ALS-M25	M25	33	38	3	10 Stk.	Metal (ML)	4031026309842	166-50121
ALS-M32	M32	41	47	3	2 Stk.	Metal (ML)	4031026309859	166-50122
ALS-M40	M40	50	58	4	1 Stk.	Metal (ML)	4031026309866	166-50123
ALS-M50	M50	63	72	4	1 Stk.	Metal (ML)	4031026309873	166-50124
ALS-M63	M63	80	92	5	1 Stk.	Metal (ML)	4031026309880	166-50125

Alle dimensioner i mm. Der tages forbehold for tekniske ændringer.
Minimum ordre antal (MOQ) kan være forskellig fra emballageindhold.