



HelaGuard tilbehør

- ALSS låsemøtrik, rustfri stål

Sekskantet ALSS låsemøtrik anvendes til sikring af fittings.




ALSS låsemøtrik i rustfri stål.

MATERIALE	Rustfrit stål type SS316
Driftstemperatur	-100 °C til +400 °C

HF ✓

RoHS ✓



HelaGuard låsemøtrik

TYPE	Møtrik str.	A/F møtrik (A/F3)	Modstående hjørner (A/C)	Tykkelse (T)	Enhed	Farve	EAN	Bestillings-nr.
ALSS-M16	M16	20	23	3,5	10 Stk.	Metal (ML)	4031026309897	166-50126
ALSS-M20	M20	24	28	3,5	10 Stk.	Metal (ML)	4031026309903	166-50127
ALSS-M25	M25	30	34	3,5	10 Stk.	Metal (ML)	4031026309910	166-50128
ALSS-M32	M32	38	43	4,5	2 Stk.	Metal (ML)	4031026309927	166-50129
ALSS-M40	M40	48	53	5,0	1 Stk.	Metal (ML)	4031026309934	166-50130
ALSS-M50	M50	60	65	6,0	1 Stk.	Metal (ML)	4031026309941	166-50131
ALSS-M63	M63	70	76	6,5	1 Stk.	Metal (ML)	4031026309958	166-50132

Alle dimensioner i mm. Der tages forbehold for tekniske ændringer.
Minimum ordre antal (MOQ) kan være forskellig fra emballageindhold.