



Fittings with swivel flange

HG-SFL Straight fitting, IP66

Straight swivel flange.

Features and benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus




HelaGuard HG-SFL Straight Swivel Flange, IP66.

MATERIAL	Polyamide 6.6 (PA66)
Operating Temperature	-50 °C to +135 °C
Flammability	UL 94 V2

HF ✓

RoHS ✓



HelaGuard fitting, straight swivel flange

TYPE	Nominal Ø	Min. Bore Size (B)	Outside Ø max (OD max.)	Length (L)	Hole Ø (FH)	Fixing Hole Centres (F)	Fixing Hole Centres (F2)	Pack Cont.	Colour	Article-No.
HG16-SFL	16	14.5	29	41	5,2	36	-	10 pcs.	Black (BK)	166-21200
HG21-SFL	21	14.5	34	44	5,2	36	-	10 pcs.	Black (BK)	166-21201
HG28-SFL	28	19.5	44	49	6,2	53	-	10 pcs.	Black (BK)	166-21202
HG34-SFL	34	26.5	51	55	6,2	36	54	10 pcs.	Black (BK)	166-21203
HG42-SFL	42	42.0	63	63	6,2	36	54	2 pcs.	Black (BK)	166-21204

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Minimum Order Quantity (MOQ) may differ from package content.