



Fittings with swivel flange

HG-45FL 45° Elbow fitting, IP66

45° elbow swivel flange.


Features and benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus



HelaGuard HG-45FL 45° Elbow Swivel Flange, IP66.

MATERIAL	Polyamide 6.6 (PA66)
Operating Temperature	-50 °C to +135 °C
Flammability	UL 94 V2



HelaGuard fitting, 45° swivel flange

TYPE	Nominal Ø	Min. Bore Size (B)	Outside Ø max (OD max.)	Length (L)	Hole Ø (FH)	Fixing Hole Centres (F)	Fixing Hole Centres (F2)	Pack Cont.	Colour	Article-No.
HG16-45FL	16	14.0	29	56	5,2	36	-	10 pcs.	Black (BK)	166-23600
HG21-45FL	21	14.0	34	63	5,2	36	-	10 pcs.	Black (BK)	166-23601
HG28-45FL	28	19.0	44	77	6,2	53	-	10 pcs.	Black (BK)	166-23602
HG34-45FL	34	24.5	51	84	6,2	36	54	10 pcs.	Black (BK)	166-23603
HG42-45FL	42	39.0	63	98	6,2	36	54	2 pcs.	Black (BK)	166-23604

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Minimum Order Quantity (MOQ) may differ from package content.