



Connectors, reducers and couplers

HGL-Y Y-Connector, IP68

Fulfils IP66, IP67, IP68 and IP69k.


Features and benefits

- Fast fit Y-shaped connector
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus



HelaGuard HGL-Y, Y-Connector with conduit seals.

MATERIAL	Polyamide 6.6 (PA66), Thermoplastic Elastomer (TPE)
Operating Temperature	-50 °C to +135 °C
Flammability	UL 94 V2



HelaGuard fitting, Y-connector

TYPE	From nominal diameter	To nominal diameter	Width (W)	Height (H)	Hole Ø (FH)	Pack Cont.	Colour	Article-No.
HGL16-Y13	16	13	49	77	4,0	5 pcs.	Black (BK)	166-25901
HGL21-Y16	21	16	59	89	5,0	3 pcs.	Black (BK)	166-25902
HGL28-Y21	28	21	67	93	6,0	3 pcs.	Black (BK)	166-25903
HGL34-Y28	34	28	90	116	6,5	2 pcs.	Black (BK)	166-25904

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.