



### Metallic conduits with liquid-tight cover

#### LTSUL, Galvanised steel conduit, PVC cover, UL listed

Flexible galvanised steel conduit including copper bonding strip (up to 40 mm) with smooth, oil resistant PVC cover. Fulfills IP66, IP67, IP68 and IP69k with LTS-fittings. LTSUL is used in machine tools and outdoor installations where UL-listing is required.

#### Features and benefits


- Liquid-tight (IP68 and IP69k with LTS fittings)
- UL-listed and CSA approved
- High compression, tensile and impact strength
- Good flexibility
- Smooth outer cover does not wrinkle when bent
- Good resistance to acids, petrol, oils and greases
- UV-resistant, suitable for outdoor use
- Colour: black



HelaGuard LTSUL.



The HelaGuard LTSUL galvanised steel conduit with a PVC Cover is UL listed and typically used on drilling platforms.



HelaGuard liquid-tight metallic conduit, plastic coating

<b>MATERIAL</b>	Galvanised Steel (GS), Polyvinylchloride (PVC), Copper (CU)
<b>Operating Temperature</b>	-15 °C to +75 °C



TYPE	Nominal Ø	US Trade Size	Outside Ø (OD)	Inside Ø (ID)	Min. Bending Radius (R)	Weight	Reel Length	Colour	Article-No.
LTSUL16	16	3/8 "	17.8	12.6	50	432 g/m	25 m	Black (BK)	166-32100
LTSUL20	20	1/2 "	21.1	16.0	90	477 g/m	25 m	Black (BK)	166-32101
LTSUL25	25	3/4 "	26.4	21.1	110	789 g/m	25 m	Black (BK)	166-32102
LTSUL32	32	1 "	33.1	26.5	140	1,221 g/m	15 m	Black (BK)	166-32103
LTSUL40	40	1 1/4 "	41.8	35.4	180	1,519 g/m	15 m	Black (BK)	166-32104
LTSUL50	50	1 1/2 "	47.9	40.4	230	1,846 g/m	15 m	Black (BK)	166-32105
LTSUL63	63	2 "	59.7	51.6	280	2,159 g/m	15 m	Black (BK)	166-32106

All dimensions in mm. Subject to technical changes.  
Other reel lengths available on request. Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval. Please check our website for latest approvals.