



### Fittings for metallic conduits with liquid-tight cover

#### LTS-LTS Compression coupler, IP68

Nickel plated brass.

Fulfils IP66, IP67, IP68 and IP69k.

#### Features and benefits

- Multipart compression coupler including polyamide seal
- Joins two conduits
- Provides excellent tensile strength




HeliaGuard LTS-LTS Compression Coupler.

|                              |                                                 |
|------------------------------|-------------------------------------------------|
| <b>MATERIAL</b>              | Nickel Plated Brass (NPB),<br>Polyamide 6 (PA6) |
| <b>Operating Temperature</b> | -50 °C to +135 °C                               |

HF ✓

RoHS ✓



HeliaGuard compression coupler

| TYPE        | Nominal<br>Ø | Min. Bore<br>Size<br>(B) | Length<br>(L) | A/F Body<br>(A/F1) | A/F Nut<br>(A/F3) | Pack<br>Cont. | Colour     | Article-No. |
|-------------|--------------|--------------------------|---------------|--------------------|-------------------|---------------|------------|-------------|
| LTS20-LTS20 | 20           | 14.5                     | 39.5          | 26                 | 29                | 10 pcs.       | Metal (ML) | 166-32600   |
| LTS25-LTS25 | 25           | 18.0                     | 46.9          | 33                 | 35                | 10 pcs.       | Metal (ML) | 166-32601   |

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content.