



Fittings for metallic conduits with plastic coating and metallic overbraid

PCSB-SM Swivel external thread, IP54

Swivel external thread, nickel plated brass.


Features and benefits

- Two-part fitting of shell and body with external thread
- External thread swivels about main body
- Provides tight, reliable hold of conduit
- Can be secured with locknut



HelasGuard PCSB-SM Swivel External Thread.

MATERIAL	Nickel Plated Brass (NPB)
Operating Temperature	-100 °C to +300 °C



HelasGuard fitting, straight with swivel external thread

TYPE	Nominal Ø	Thread Size	Min. Bore Size (B)	Length (L)	A/F Body (A/F1)	A/F Thread (A/F2)	A/F Nut (A/F3)	Thread Length (TL)	Pack Cont.	Colour	Article-No.
PCSB12-SM-M16	12	M16	8.5	36.2	17	17	17	9.0	10 pcs.	Metal (ML)	166-33900
PCSB12-SM-PG9	12	PG9	8.5	36.2	17	17	17	9.0	10 pcs.	Metal (ML)	166-33908
PCSB16-SM-M16	16	M16	11.5	38.1	20	20	20	10.0	10 pcs.	Metal (ML)	166-33901
PCSB16-SM-M20	16	M20	11.5	38.1	20	22	20	10.0	10 pcs.	Metal (ML)	166-33902
PCSB16-SM-PG11	16	PG11	11.5	38.1	20	20	20	10.0	10 pcs.	Metal (ML)	166-33909
PCSB20-SM-M20	20	M20	15.3	40.0	26	24	24	10.0	10 pcs.	Metal (ML)	166-33903
PCSB20-SM-PG16	20	PG16	15.3	40.0	26	24	24	10.0	10 pcs.	Metal (ML)	166-33910
PCSB25-SM-M25	25	M25	19.1	47.2	30	29	29	12.0	10 pcs.	Metal (ML)	166-33904
PCSB25-SM-PG21	25	PG21	19.1	47.2	30	29	29	12.0	10 pcs.	Metal (ML)	166-33911
PCSB32-SM-M32	32	M32	26.0	52.6	38	38	38	13.0	2 pcs.	Metal (ML)	166-33905
PCSB32-SM-PG29	32	PG29	26.0	52.6	38	38	38	13.0	2 pcs.	Metal (ML)	166-33912
PCSB40-SM-M40	40	M40	34.6	57.8	50	48	48	14.0	1 pc.	Metal (ML)	166-33906
PCSB40-SM-PG36	40	PG36	34.6	57.8	50	48	48	14.0	1 pc.	Metal (ML)	166-33913
PCSB50-SM-M50	50	M50	44.7	60.2	60	58	58	15.0	1 pc.	Metal (ML)	166-33907
PCSB50-SM-PG42	50	PG42	44.7	60.2	60	58	58	15.0	1 pc.	Metal (ML)	166-33914

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.