



Fittings for metallic conduits and metallic overbraid

SCSB-FM Fixed external thread, IP40

Fixed external thread, nickel plated brass.

Features and benefits

- Two-part fitting of shell and body with external thread
- Provides tight, reliable hold of conduit
- Can be secured with locknut




HelaGuard SCSB-FM Fixed External Thread.

MATERIAL	Nickel Plated Brass (NPB)
Operating Temperature	-100 °C to +300 °C

HF ✓

RoHS ✓



HelaGuard fitting, straight with fixed external thread

TYPE	Nominal Ø	Thread Size	Min. Bore Size (B)	Length (L)	A/F Body (A/F1)	A/F Nut (A/F3)	Thread Length (TL)	Pack Cont.	Colour	Article-No.
SCSB12-FM-M16	12	M16	8.5	28.0	17	17	10.0	10 pcs.	Metal (ML)	166-34600
SCSB12-FM-PG9	12	PG9	8.5	28.0	17	17	10.0	10 pcs.	Metal (ML)	166-34607
SCSB16-FM-M16	16	M16	11.5	28.0	20	20	10.0	10 pcs.	Metal (ML)	166-34601
SCSB16-FM-M20	16	M20	11.5	28.0	22	20	10.0	10 pcs.	Metal (ML)	166-34602
SCSB16-FM-PG11	16	PG11	11.5	28.0	20	20	10.0	10 pcs.	Metal (ML)	166-34608
SCSB20-FM-M20	20	M20	15.3	30.8	24	26	10.0	10 pcs.	Metal (ML)	166-34603
SCSB20-FM-PG16	20	PG16	15.3	30.8	24	26	10.0	10 pcs.	Metal (ML)	166-34609
SCSB25-FM-M25	25	M25	19.1	32.5	29	29	10.0	10 pcs.	Metal (ML)	166-34604
SCSB25-FM-PG21	25	PG21	19.1	32.5	29	29	10.0	10 pcs.	Metal (ML)	166-34610
SCSB32-FM-M32	32	M32	26.0	39.3	36	38	13.0	2 pcs.	Metal (ML)	166-34605
SCSB32-FM-PG29	32	PG29	26.0	39.3	36	38	13.0	2 pcs.	Metal (ML)	166-34611
SCSB40-FM-M40	40	M40	34.6	42.8	48	48	14.0	1 pc.	Metal (ML)	166-34606
SCSB40-FM-PG36	40	PG36	34.6	42.8	48	48	14.0	1 pc.	Metal (ML)	166-34612
SCSB50-FM-M50	50	M50	44.7	48.0	58	58	15.0	1 pc.	Metal (ML)	166-34613

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.