



Fittings for metallic conduits and metallic overbraid

SCSB-PC Plain hole connector, IP40

Plain hole connector, nickel plated brass.


Features and benefits

- Two part fitting of shell and body without thread
- Acts as a locking device
- The body is fitted to the conduit through the opposite side of the entry
- Provides a smooth entry bush



HelaGuard SCSB-PC Plain Hole Connector.

MATERIAL	Nickel Plated Brass (NPB)
Operating Temperature	-100 °C to +300 °C



HelaGuard fitting, plain hole connector

TYPE	Nominal Ø	Min. Bore Size (B)	Length (L)	A/F Body (A/F1)	A/F Nut (A/F3)	Pack Cont.	Colour	Article-No.
SCSB12-PC	12	8.5	18.0	17	17	10 pcs.	Metal (ML)	166-34800
SCSB16-PC	16	11.5	18.9	20	20	10 pcs.	Metal (ML)	166-34801
SCSB20-PC	20	15.3	21.0	24	26	10 pcs.	Metal (ML)	166-34802
SCSB25-PC	25	19.1	23.5	29	29	10 pcs.	Metal (ML)	166-34803
SCSB32-PC	32	26.0	26.3	38	38	2 pcs.	Metal (ML)	166-34804
SCSB40-PC	40	34.6	28.8	48	48	1 pc.	Metal (ML)	166-34805

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.