



Non-Metallic Conduits

HG-HW PA6 Heavy Weight

Heavy weight corrugated flexible conduit for high mechanical demands, including heavy-duty machine building, plant construction, and public buildings.


Features and benefits

- Heavy weight
- High mechanical strength
- Very abrasion resistant
- High impact strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus
- Self-extinguishing according to UL94 V2
- Colour: black



HelaGuard HG-HW for very high mechanical protection.

MATERIAL	Polyamide 6 (PA6)
Operating Temperature	-40 °C to +120 °C
Flammability	UL 94 V2



HelaGuard non-metallic conduit

TYPE	Nominal Ø	NW Ø	Outside Ø (OD)	Inside Ø (ID)	Min. Bending Radius (R)	Weight	Reel Length	Colour	Article-No.
HG-HW13	13	10	13.0	9.0	35	37 g/m	50 m	Black (BK)	166-11302
HG-HW16	16	12	15.8	11.5	45	48 g/m	50 m	Black (BK)	166-11303
HG-HW21	21	17	21.2	15.5	55	80 g/m	50 m	Black (BK)	166-11304
HG-HW28	28	23	28.5	21.3	60	130 g/m	50 m	Black (BK)	166-11305
HG-HW34	34	29	34.5	26.9	70	170 g/m	25 m	Black (BK)	166-11306
HG-HW42	42	36	42.5	34.6	80	200 g/m	25 m	Black (BK)	166-11307
HG-HW54	54	48	54.5	46.0	90	270 g/m	25 m	Black (BK)	166-11308

All dimensions in mm. Subject to technical changes.
Other reel lengths available on request. Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval. Please check our website for latest approvals.



Add items to your watchlist!

www.HT.click/52-13

