



Non-Metallic Conduits

HG-PP PP Conduit

Standard weight conduit made of Polypropylen is used in machine building, electrical installations and buildings, often in concrete or plaster.


Features and benefits

- Very flexible
- Abrasion resistant
- Resistant to acids and alkalis
- Self-extinguishing to IEC 61386



HelaGuard PP Standard is typically used in electrical installations and buildings.

MATERIAL	Polypropylene (PP)
Operating Temperature	-20 °C to +90 °C
Flammability	self-extinguishing according to EN IEC 61386



HelaGuard non-metallic conduit

RoHS

TYPE	Nominal Ø	NW Ø	Outside Ø (OD)	Inside Ø (ID)	Min. Bending Radius (R)	Weight	Reel Length	Colour	Article-No.
HG-PP10	10	7.5	10.0	6.3	15	16 g/m	50 m	Black (BK)	166-11900
HG-PP13	13	10	13.0	9.8	25	20 g/m	50 m	Black (BK)	166-11901
HG-PP16	16	12	15.8	11.8	35	30 g/m	50 m	Black (BK)	166-11902
HG-PP20	20	16	20.0	14.8	40	45 g/m	50 m	Black (BK)	166-11903
HG-PP21	21	17	21.2	16.7	40	50 g/m	50 m	Black (BK)	166-11904
HG-PP25	25	22	25.0	19.1	50	52 g/m	50 m	Black (BK)	166-11905
HG-PP26	26	22	25.4	21.4	50	52 g/m	50 m	Black (BK)	166-11906
HG-PP28	28	23	28.5	22.8	55	65 g/m	50 m	Black (BK)	166-11907
HG-PP34	34	29	34.5	28.1	65	90 g/m	25 m	Black (BK)	166-11908
HG-PP42	42	36	42.5	35.5	80	120 g/m	25 m	Black (BK)	166-11909
HG-PP54	54	48	54.5	47.2	100	150 g/m	25 m	Black (BK)	166-11910
HG-PP67	67	56	67.2	56.3	150	250 g/m	10 m	Black (BK)	166-11911

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Other reel lengths available on request. Minimum Order Quantity (MOQ) may differ from package content.



Add items to your watchlist!

www.HT.click/52-17

