



Fittings with fixed external thread

HG-45 45° Elbow fitting, IP66

45° elbow external thread.

Features and benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus
- Metric threads supplied with locknuts



HeliaGuard HG-45 45° Elbow, IP66.




Fittings with UNEF and NPT threads available on request. Please contact us!

MATERIAL	Polyamide 6.6 (PA66)
Operating Temperature	-50 °C to +135 °C
Flammability	UL 94 V2

HF ✓

RoHS ✓



HeliaGuard fitting, 45° with fixed external thread

TYPE	Nominal Ø	Thread Size	Min. Bore Size (B)	Outside Ø max (OD max.)	Length (L)	Face Diameter (FD)	Thread Length (TL)	Pack Cont.	Colour	Article-No.
HG16-45-M20	16	M20	14.0	29	58	27	13	10 pcs.	Black (BK)	166-23400
HG16-45-PG13	16	PG13,5	14.0	29	58	26	11	10 pcs.	Black (BK)	166-23406
HG21-45-M20	21	M20	14.0	32	61	27	13	10 pcs.	Black (BK)	166-23401
HG21-45-PG13	21	PG13,5	14.0	32	61	26	11	10 pcs.	Black (BK)	166-23407
HG21-45-PG16	21	PG16	14.0	32	61	27	11	10 pcs.	Black (BK)	166-23408
HG28-45-M25	28	M25	19.0	44	73	32	15	10 pcs.	Black (BK)	166-23402
HG28-45-PG21	28	PG21	19.0	44	73	35	12	10 pcs.	Black (BK)	166-23409
HG34-45-M32	34	M32	24.5	51	81	40	16	10 pcs.	Black (BK)	166-23403
HG34-45-PG29	34	PG29	24.5	51	81	44	12	10 pcs.	Black (BK)	166-23410
HG42-45-M50	42	M50	39.0	63	98	60	16	2 pcs.	Black (BK)	166-23404
HG42-45-PG36	42	PG36	39.0	63	98	57	12	2 pcs.	Black (BK)	166-23411
HG54-45-M50	54	M50	39.0	76	106	60	16	2 pcs.	Black (BK)	166-23405

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Minimum Order Quantity (MOQ) may differ from package content.

