



Connectors, reducers and couplers

HGL-R Reducer, IP68

Features and benefits

- Reduce size of connector to attach smaller size conduits
- Used with T-Connector and Y-Connectors
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus




HGL-R Reducer with conduit seal, IP68.

MATERIAL	Polyamide 6.6 (PA66), Thermoplastic Elastomer (TPE)
Operating Temperature	-50 °C to +135 °C

HF ✓

RoHS ✓



HelaGuard fitting, reducer

TYPE	From nominal diameter	To nominal diameter	Min. Bore Size (B)	Outside Ø max (OD max.)	Length (L)	Length (L2)	Face Diameter (FD)	Pack Cont.	Colour	Article-No.
HGL13-R16	16	13	11.7	24	43	17	23	10 pcs.	Black (BK)	166-25100
HGL16-R21	21	16	14.5	29	51	23	30	5 pcs.	Black (BK)	166-25101
HGL16-R28	28	16	14.5	29	57	29	34	5 pcs.	Black (BK)	166-25103
HGL16-R34	34	16	14.5	29	58	30	44	5 pcs.	Black (BK)	166-25106
HGL21-R28	28	21	17.5	32	59	29	34	5 pcs.	Black (BK)	166-25102
HGL21-R34	34	21	17.5	32	60	30	44	5 pcs.	Black (BK)	166-25105
HGL21-R42	42	21	17.5	32	60	30	50	3 pcs.	Black (BK)	166-25109
HGL28-R34	34	28	25.7	44	65	30	44	5 pcs.	Black (BK)	166-25104
HGL28-R42	42	28	25.7	44	60	30	50	3 pcs.	Black (BK)	166-25108
HGL34-R42	42	34	31.5	51	67	30	50	3 pcs.	Black (BK)	166-25107

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

