



## Fittings for metallic conduits

### SC-PC Plain hole connector, IP40

Plain hole connector, nickel plated brass.


#### Features and benefits

- Two part fitting of shell and body without thread
- Acts as a locking device
- The body is fitted to the conduit through the opposite side of the entry
- Provides a smooth entry bush



HelaGuard SC-PC Plain Hole Connector.

|                              |                           |
|------------------------------|---------------------------|
| <b>MATERIAL</b>              | Nickel Plated Brass (NPB) |
| <b>Operating Temperature</b> | -100 °C to +300 °C        |



HelaGuard fitting, plain hole connector

| TYPE    | Nominal Ø | Min. Bore Size (B) | Length (L) | A/F Body (A/F1) | Pack Cont. | Colour     | Article-No. |
|---------|-----------|--------------------|------------|-----------------|------------|------------|-------------|
| SC10-PC | 10        | 5.6                | 15.0       | 13              | 10 pcs.    | Metal (ML) | 166-30500   |
| SC12-PC | 12        | 8.5                | 15.5       | 17              | 10 pcs.    | Metal (ML) | 166-30501   |
| SC16-PC | 16        | 11.5               | 20.0       | 20              | 10 pcs.    | Metal (ML) | 166-30502   |
| SC20-PC | 20        | 15.3               | 16.5       | 24              | 10 pcs.    | Metal (ML) | 166-30503   |
| SC25-PC | 25        | 19.1               | 20.5       | 29              | 10 pcs.    | Metal (ML) | 166-30504   |
| SC32-PC | 32        | 26.2               | 23.5       | 38              | 2 pcs.     | Metal (ML) | 166-30505   |
| SC40-PC | 40        | 34.2               | 24.8       | 48              | 2 pcs.     | Metal (ML) | 166-30506   |
| SC50-PC | 50        | 44.8               | 30.0       | 58              | 1 pc.      | Metal (ML) | 166-30507   |
| SC63-PC | 63        | 54.5               | 33.5       | 70              | 1 pc.      | Metal (ML) | 166-30508   |
| SC75-PC | 75        | 66.5               | 42.0       | 84              | 1 pc.      | Metal (ML) | 166-30509   |

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.

