



Fittings for metallic conduits

SC-FF Fixed internal thread, IP40

Fixed internal thread, nickel plated brass.


Features and benefits

- Two-part fitting of shell and body with internal thread
- Provides tight, reliable hold of conduit
- Can be used to couple two conduits together when used with swivel fitting



HelaGuard SC-FF Fixed Internal Thread.

MATERIAL	Nickel Plated Brass (NPB)
Operating Temperature	-100 °C to +300 °C



HelaGuard fitting, straight with fixed internal thread

TYPE	Nominal Ø	Thread Size	Min. Bore Size (B)	Length (L)	A/F Body (A/F1)	Thread Length (TL)	Pack Cont.	Colour	Article-No.
SC16-FF-M20	16	M20	11.5	24.5	22	10.0	10 pcs.	Metal (ML)	166-30600
SC20-FF-M20	20	M20	15.3	26.0	24	10.0	10 pcs.	Metal (ML)	166-30601
SC25-FF-M25	25	M25	19.1	30.0	29	12.0	10 pcs.	Metal (ML)	166-30602
SC32-FF-M32	32	M32	26.2	33.3	36	13.0	2 pcs.	Metal (ML)	166-30603

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



Add items to your watchlist!

www.HT.click/52-71

