



Fittings for metallic conduits with plastic coating

PCS-90FMC 90° Elbow compression fitting, IP65

External thread, nickel plated brass.

Fulfils IP65.

Features and benefits

- Multipart 90° compression fitting including elastomeric seal
- Provides excellent tensile strength




HelaGuard PCS-90FMC 90° Elbow Compression Fitting.

MATERIAL	Nickel Plated Brass (NPB), Polyamide 6 (PA6)
Operating Temperature	-50 °C to +135 °C

HF ✓

RoHS ✓



HelaGuard compression fitting, 90° with fixed external thread

TYPE	Nominal Ø	Thread Size	Min. Bore Size (B)	A/F Body (A/F1)	A/F Nut (A/F3)	Thread Length (TL)	Pack Cont.	Colour	Article-No.
PCS12-90FMC-M16	12	M16	8.6	20	22	10.0	10 pcs.	Metal (ML)	166-31601
PCS16-90FMC-M16	16	M16	11.5	20	26	10.0	10 pcs.	Metal (ML)	166-31602
PCS16-90FMC-M20	16	M20	11.5	24	26	13.0	10 pcs.	Metal (ML)	166-31603
PCS20-90FMC-M20	20	M20	15.3	24	29	13.0	10 pcs.	Metal (ML)	166-31604
PCS25-90FMC-M25	25	M25	19.1	30	35	14.0	10 pcs.	Metal (ML)	166-31605
PCS32-90FMC-M32	32	M32	26.0	36	42	15.0	2 pcs.	Metal (ML)	166-31606

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



Add items to your watchlist!

www.HT.click/52-79

