



Fittings for metallic conduits with liquid-tight cover

LTS-90FMC 90° Elbow compression fitting, IP68

External thread, nickel plated brass.

Fulfils IP66, IP67, IP68 and IP69k.


Features and benefits

- Multipart 90° compression fitting including polyamide seal
- Provides excellent tensile strength



HelaGuard LTS-90FMC 90° Elbow Compression Fitting.

MATERIAL	Nickel Plated Brass (NPB), Polyamide 6 (PA6)
Operating Temperature	-50 °C to +135 °C



HelaGuard compression fitting, 90° with fixed external thread

TYPE	Nominal Ø	Thread Size	Min. Bore Size (B)	A/F Body (A/F1)	A/F Nut (A/F3)	Thread Length (TL)	Pack Cont.	Colour	Article-No.
LTS12-90FMC-M16	12	M16	8.6	20	22	10.0	10 pcs.	Metal (ML)	166-32400
LTS16-90FMC-M16	16	M16	10.7	20	26	10.0	10 pcs.	Metal (ML)	166-32401
LTS16-90FMC-M20	16	M20	10.7	24	26	13.0	10 pcs.	Metal (ML)	166-32402
LTS20-90FMC-M20	20	M20	14.5	24	29	13.0	10 pcs.	Metal (ML)	166-32403
LTS25-90FMC-M25	25	M25	18.0	30	35	14.0	10 pcs.	Metal (ML)	166-32404
LTS32-90FMC-M32	32	M32	24.6	36	42	15.0	2 pcs.	Metal (ML)	166-32405
LTS40-90FMC-M40	40	M40	32.7	46	52	18.0	1 pc.	Metal (ML)	166-32406
LTS50-90FMC-M50	50	M50	37.7	57	58	18.0	1 pc.	Metal (ML)	166-32407
LTS63-90FMC-M63	63	M63	49.0	72	70	20.0	1 pc.	Metal (ML)	166-32408

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content.

