



Fittings for spiral-reinforced PVC conduits

PSRSC-90FMC 90° compression fitting

90° fitting, fixed external thread, nickel plated brass.

Fulfills IP66, IP67, IP68 and IP69k with PSRSC conduits.

Features and benefits

- Multipart 90° compression fitting including elastomeric
- Can be used for knockouts or threaded entries as fitting rotates until tightened
- Fits PSRSC conduits




HeliaGuard PSRSC-90FMC 90° Elbow Compression Fitting.

MATERIAL	Nickel Plated Brass (NPB), Polyamide 6 (PA6)
Operating Temperature	-50 °C to +135 °C

HF ✓

RoHS ✓



HeliaGuard compression fitting, 90° with fixed external thread

TYPE	Nominal Ø	Thread Size	Min. Bore Size (B)	A/F Body (A/F1)	A/F Nut (A/F3)	Thread Length (TL)	Pack Cont.	Colour	Article-No.
PSRSC12-90FMC-M16	12	M16	8.6	20	22	10.0	10 pcs.	Metal (ML)	166-41201
PSRSC16-90FMC-M16	16	M16	10.7	20	26	10.0	10 pcs.	Metal (ML)	166-41202
PSRSC16-90FMC-M20	16	M20	10.7	24	26	13.0	10 pcs.	Metal (ML)	166-41203
PSRSC20-90FMC-M20	20	M20	14.5	24	29	13.0	10 pcs.	Metal (ML)	166-41204
PSRSC25-90FMC-M25	25	M25	18.0	30	35	14.0	10 pcs.	Metal (ML)	166-41205
PSRSC32-90FMC-M32	32	M32	24.6	36	42	15.0	2 pcs.	Metal (ML)	166-41206
PSRSC40-90FMC-M40	40	M40	32.7	46	52	18.0	1 pc.	Metal (ML)	166-41207
PSRSC50-90FMC-M50	50	M50	37.7	57	58	18.0	1 pc.	Metal (ML)	166-41208
PSRSC63-90FMC-M63	63	M63	49.0	72	70	20.0	1 pc.	Metal (ML)	166-41209

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

