



Heat shrinkable tubing 2:1 - PVC

LVR

LVR can be used for cable joints, low voltage bus bars and batteries.

Features and benefits

- PVC heat shrinkable tubing
- Self-extinguishing
- Good chemical resistance and mechanical protection



LVR used for mechanical protection.

MATERIAL	Flexible Polyvinyl Chloride, cadmium free (PVC)
Shrink Ratio	2:1
Operating Temperature	-30 °C to +105 °C
Min. Shrink Temperature	+80 °C
Longitudinal Change After Shrinkage	+/-10% max
Dielectric Strength	22 kV/mm
Shelf Life	12 Months max.
Storage Temperature	+25 °C max.
Flammability	self-extinguishing, UL 224 VW-1



Heat Shrinkable Tubing 2:1

RoHS

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Tools	Article-No.
LVR-2.4/1.2	2.4	1.2	0.40	250 m	Black (BK)	30	344-00240
LVR-3.2/1.6	3.2	1.6	0.40	250 m	Black (BK)	30	344-00320
LVR-4.8/2.4	4.8	2.4	0.50	250 m	Black (BK)	30	344-00480
LVR-6.4/3.2	6.4	3.2	0.60	250 m	Black (BK)	30	344-00640
LVR-9.5/4.8	9.5	4.8	0.60	125 m	Black (BK)	30	344-00950
LVR-12.7/6.4	12.7	6.4	0.70	75 m	Black (BK)	30	344-01270
LVR-19.1/9.5	19.0	9.5	0.80	100 m	Black (BK)	30	344-01900
LVR-25.4/12.7	25.4	12.7	1.00	100 m	Black (BK)	30	344-02540

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools	
	30 H6100
	566

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!

www.HT.click/49-232

