



Two-Component Adhesive for Heat Shrinkable Tubing and Shapes

V9500

Features and benefits

- High performance, two-part epoxy adhesive
- Very resistant to most solvents and fuels, even at elevated temperatures
- Two different packages available
- V9500 available in 10g bags for manual mixing
- Processing set: emery paper, small mixing bowl and wooden spatula
- High performance bonding
- Meets military requirements for heat shrinkable components for harnesses
- VG-approved



V9500 - VG 95343 approved 2K Epoxy Adhesive Kit.



www.HellermannTyton.co.uk/V9500-cat22



The V9500 applicator gun guarantees the clean and precise coating of special fittings.

| | |
|------------------------------|---------------------------------------|
| MATERIAL | Epoxy resins (EP) |
| Colour | Black (BK) |
| Curing Temperature | +135 °C |
| Curing Time | 24 hours at +25 °C, 2 hours at +85 °C |
| Operating Temperature | -75 °C to +150 °C |



| TYPE | Description | Designation as per VG-Norm | Tools | Article-No. |
|--------------------------------|--------------------------------------------------------------------------------|----------------------------|-------|-------------|
| V9500 Epoxy Kit | 5 x 10g sachets (50g), 5 x mixing pots, 5 x mixing sticks, 5 x emery papers | VG 95343 T15 A001 A | 30 | 627-95000 |
| | 1 x dual cartridge (50g), 5 x mixing pots, 5 x mixing sticks, 5 x emery papers | VG 95343 T15 A 002 B | 30 | 627-95001 |
| V9500 Epoxy Cartridge | Two-component adhesive cartridge | VG 95343 T15 D 002 B | 30 | 627-95002 |
| V9500 Applicator Gun | Applicator gun | VG 95343 T15 DA | - | 627-95003 |
| V9500 Applicator Nozzle | Mixing nozzle | VG 95343 T15 MA | - | 627-95004 |

All dimensions in mm. Subject to technical changes.

| Recommended Tools | |
|-------------------|-------------|
| | 30 H6100 |
| | 566 |

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!

www.HT.click/49-303

