



Self-amalgamating Tapes – Vinyl Mastic Tape

HelaTape Power 670 VM

Features and benefits

- Easy to apply vinyl mastic tape
- Self-adhesive application - without stretching
- Mastic layer is very sticky and provides excellent moisture sealing
- Vinyl top layer provides additional protection
- Performs continuously. Even at low temperatures
- Primary insulation up to 1 kV
- Applicable to all extruded cable insulations
- UV and weather resistant



HelaTape Power 670 provides additional vinyl film protection to the mastic compound.

| | |
|---|---|
| MATERIAL | Polyvinylchloride (PVC), Isobutene-Isoprene-Rubber (butyl rubber) (IIR) |
| Operating Temperature | -30 °C to +80 °C |
| Intermittent Operating Temperature | +95 °C |
| Water Absorption | 0.9 % |
| Tensile Strength | 16 N/mm ² |
| Elongation at break | 200 % |
| Volume Resistance | 10 ¹² Ω cm |
| Dielectric Strength | 19.7 kV/mm |

HF ✓

RoHS ✓

| TYPE | Thickness (T) | Width (W) | Length (L) | Colour | Article-No. |
|--------------------|---------------|-----------|------------|------------|-------------|
| HTAPE-POWER 670-VM | 1.20 | 100.0 | 3.0 m | Black (BK) | 711-00304 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

