



## Connectors - For all Types of Wire

### HelaCon Plus Releasable

The HelaCon Plus Releasable connectors are used for all types of wire to connect cable and conductors in the field of electrical installation. The connectors can be used in all kinds of junction boxes either on-wall or flush-mounted. HelaCon offers the best possible solution when convenient processing and maximum safety is required.

#### Features and benefits

- Universal push-in wire connector for solid, stranded and fine-stranded wires
- Compact size connector
- Wire clamping range: 0.2 - 4.0 mm<sup>2</sup>
- Separate voltage test entry on the top
- For proper fixing that can be visually checked through transparent housing
- Safe application, installation and maintenance



[www.HellermannTyton.co.uk/HelaCon-Plus-Releasable-cat22](http://www.HellermannTyton.co.uk/HelaCon-Plus-Releasable-cat22)



HelaCon Plus Releasable Box and Blister 2.

| MATERIAL                            | Polycarbonate (PC)                           |
|-------------------------------------|----------------------------------------------|
| Max Current                         | 32 A                                         |
| Max Voltage                         | 450 V                                        |
| Wire Range (VDE) in mm <sup>2</sup> | 0.2 to 4.0 mm <sup>2</sup> all types of wire |
| Stripping Length                    | 10 mm                                        |
| Flammability                        | UL 94 V0                                     |
| Operating Temperature               | -30 °C to +85 °C                             |

HF ✓

RoHS ✓

| TYPE           | Drawing | Number of Conductors | Colour           | Width (W) | Height (H) | Length (L) | Pack Cont. | Article-No. |
|----------------|---------|----------------------|------------------|-----------|------------|------------|------------|-------------|
| HCRN-2-Blister |         | 2                    | Transparent (CL) | 20.5      | 14.0       | 12.0       | 10 pcs.    | 148-90062   |
| HCRN-2         |         | 2                    | Transparent (CL) | 20.5      | 14.0       | 12.0       | 80 pcs.    | 148-90059   |
| HCRN-3-Blister |         | 3                    | Transparent (CL) | 20.5      | 14.0       | 17.0       | 8 pcs.     | 148-90063   |
| HCRN-3         |         | 3                    | Transparent (CL) | 20.5      | 14.0       | 17.0       | 50 pcs.    | 148-90060   |
| HCRN-5-Blister |         | 5                    | Transparent (CL) | 20.5      | 14.0       | 26.0       | 5 pcs.     | 148-90064   |
| HCRN-5         |         | 5                    | Transparent (CL) | 20.5      | 14.0       | 26.0       | 30 pcs.    | 148-90061   |

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!

[www.HT.click/49-414](http://www.HT.click/49-414)

