

Labels for control panel identification, thermal transfer

Helatag 1216 (White) for rough surfaces

These labels are suitable for the permanent identification of components and preassembled units within electrical industry as well as asset identification. Print with HellermannTyton's premium range of thermal transfer printers and ribbons for optimum print results. They can also be used in the design and setup as well as in the repair and expansion of control cabinets and control units.

Features and benefits

- Suited to labelling electrical panels
- White labels give excellent contrast
- Also suitable for critical surfaces
- Rounded corners ensure better long term durability of adhesion




Clear and permanent identification.

MATERIAL	Type 1216, Polyethylene, white (1216)
Operating Temperature	-30 °C to +80 °C
Curing Temperature	from 0 °C
Adhesive	Acrylic
Thickness of Foil	105 µm
Chem. Material Properties	Resistant to water, alcohol, most oils, greases, fuel, aliphatic solvents, weak acids, salts and alkalis.
Recommended Ribbon Type	TT822OUT
Thermal Transfer Printer	TT431, TT4030

HF ✓

RoHS ✓



TYPE	Width (W)	Height (H)	Width of Liner (WL)	Labels per Row	Pack Cont.	Colour	Article-No.
TAG05-08TC-1216-WH	5.0	8.0	85.0	16 pcs.	25,000 pcs.	White (WH)	596-12147
TAG05-15TC-1216-WH	5.0	15.0	85.0	16 pcs.	25,000 pcs.	White (WH)	596-12151
TAG06-10TC-1216-WH	6.0	10.0	85.0	13 pcs.	25,000 pcs.	White (WH)	596-12149
TAG08-15TC-1216-WH	8.0	15.0	85.0	10 pcs.	25,000 pcs.	White (WH)	596-12152

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.



Add items to your watchlist!

www.HT.click/49-501

