



### Helafix Tool

**HCT1 for carrier size HCR09**

**HCT2 for carrier size HCR12**

HCT1 and HCT2 tools are ideal for cleanly cutting the carrier strip as well as punching out the securing holes. For HCR06, HCR18 and HCR24, the front part of the pliers can be used. To fix the character holders HC and HCR simply use the T18 range of cable ties, fixings or rivets.

#### Features and benefits

- Cleanly cut Helafix HCR carrier tubing
- Punch securing holes on edges of HCR09 (HCT1) and HCR12 (HCT2)
- Apply punched HCR09 and HCR12 with T18 range of cable ties
- Suitable for punching rivet holes in HCR06, HCR18 and HCR24 tubing
- Punch hole diameter 2.5 mm
- Fix with T18 range of cable ties or suitable rivets



*Any length can be used...*



*...just cut to suit.*

| TYPE | For Carrier Width | For Size | Ø (D) | Article-No. |
|------|-------------------|----------|-------|-------------|
| HCT1 | 10.0              | HCR09    | 2.5   | 525-00010   |
| HCT2 | 13.0              | HCR12    | 2.5   | 525-00013   |

All dimensions in mm. Subject to technical changes.



Add items to your watchlist!  
[www.HT.click/49-571](http://www.HT.click/49-571)

