Storage rack for HIS-Boxes

HIS-Service Station

HIS general purpose heat shrink tubing provides a reliable insulation and protects against corrosion and mechanical influences. The handy dispenser is ideal for small and medium size projects on-site. The sturdy metal HIS-Service Station comes with a cutter and can store all sizes and colours. The Service Station can be mounted to the wall in the work shop or service-van.

Features and benefits

- Contains up to 5 dispenser boxes
- · Place on bench or mount to wall
- Special cutter included for easily cutting tubing length to size



HIS-Service Station contains 5 dispensers and a special cutter.

TYPE	Description	Tools	Article-No.
HIS-Service Station	HIS-Service Station incl. cutter, contents: 5 dispensers HIS-3 (shrink ratio: 3:1), black, sizes are as follows: HIS-3/1, HIS-6/2, HIS-12/4 (2 pcs.), HIS-24/8	30;32	365-30100
	HIS-Service Station incl. cutter, empty	-	300-30000

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content.

Heat shrinkable tubing 2:1 on a reel

HIS-PACK is used in general purpose of electrical insulation with a high level of protection against corrosion and mechanical abrasion.

Features and benefits

- Cross-linked Polyolefin, thin-wall and flexible
- Handy dispenser box including table showing application size range
- Available in black, red, blue, transparent and yellow/green
- 10 sizes from 1.2 mm to 25.4 mm
- · Transparent color is halogenfree



HIS-Pack.

MATERIAL	Polyolefin, cross-linked (PO-X)	
Shrink Ratio	2:1	
Operating Temperature	-55 °C to +125 °C	
Min. Shrink Temperature	+100 °C	
Longitudinal Change After Shrinkage	+/-5 %	
Dielectric Strength	20 kV/mm	
Flammability	self-extinguishing (except transparent), UL 224 VW-1 (except transparent)	





For product specific approvals and specifications please refer to the Appendix.



