

Heat shrinkable tubing 4:1 - Flame retardant

HA40 - thick wall adhesive lined

Designed for low voltage cable joints and terminations in shipbuilding. Insulates and protects against moisture.


Features and benefits

- Thick wall adhesive lined shrink tubing for low voltage power cables
- Designed for shipbuilding, Germanische Lloyd approved
- Flame retarded
- UV and weather resistant
- Excellent mechanical performance



HA40 thick wall, adhesive lined and flame retarded tubing for shipbuilding applications.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	up to 4:1
Operating Temperature	-55 °C to +110 °C
Min. Shrink Temperature	+120 °C
Softening Point Adhesive	+85 °C
Longitudinal Change After Shrinkage	-10 % max.
Dielectric Strength	15 kV/mm
Flammability	self-extinguishing



Heat Shrinkable Tubing 4:1 with adhesive

LFH ✓

RoHS ✓

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Length (L)	Colour	Tools	Article-No.
HA40-9/3	9.0	3.0	2.00	1.0 m	Black (BK)	32	321-00100
HA40-13/4	13.0	4.0	2.20	1.0 m	Black (BK)	30	321-00101
HA40-22/6	22.0	6.0	2.70	1.0 m	Black (BK)	32	321-00102
HA40-33/8	33.0	8.0	3.20	1.0 m	Black (BK)	32	321-00103
HA40-40/12	40.0	12.0	4.10	1.0 m	Black (BK)	32	321-00104
HA40-55/16	55.0	16.0	4.10	1.0 m	Black (BK)	32	321-00105
HA40-75/22	75.0	22.0	4.10	1.0 m	Black (BK)	32	321-00106
HA40-92/25	92.0	25.0	4.20	1.0 m	Black (BK)	32	321-00107

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools		
	30	32
	H6100	CHG900
	564	563

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!
www.HT.click/9-261

