



Heat shrinkable tubing 4:1 - 1.2 m lengths

SA47-LA - standard wall adhesive lined for perfect corrosion protection

SA47-LA is a semi-rigid halogen free polyolefin tubing with an inner liner of hot melt adhesive. It has excellent tensile strength and strain relief. The adhesive liner provides excellent moisture protection. Ideal for electrical connections and splices in automobiles. Tubing is transparent and hot melt adhesive is black.

SA47-LA is specially designed with less adhesive for cable connections.

Features and benefits

- Flexible, standard wall polyolefin heat shrink tubing
- Best corrosion protection available
- Excellent tensile strength and strain relief
- Provides excellent moisture protection
- Tubing is clear and hot melt adhesive black
- Provides an environmental sealing of complex parts
- Halogen free



**Cut lengths available on request.
Please contact us!**



SA47-LA - High performance heat shrink tubing.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	4:1
Operating Temperature	-40 °C to +125 °C
Min. Shrink Temperature	+130 °C
Melting Point	starting from +110 °C
Longitudinal Change After Shrinkage	-10 % max.
Dielectric Strength	>20 kV/mm
Shelf Life	5 years

HF ✓

RoHS ✓



Heat Shrinkable Tubing 4:1 with adhesive



Available with transparent inner adhesive on request.

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Length (L)	Colour	Tools	Article-No.
SA47-LA 5.75/1.25	5.75	1.25	1.15	1.2 m	Transparent (CL), Black (BK)	30;32	301-10020
SA47-LA 7.5/1.65	7.5	1.65	1.40	1.2 m	Transparent (CL), Black (BK)	30;32	301-10021
SA47-LA 11.0/2.4	11.0	2.4	1.80	1.2 m	Transparent (CL), Black (BK)	30;32	301-10022
SA47-LA 18.3/4.35	18.3	4.35	2.20	1.2 m	Transparent (CL), Black (BK)	30;32	301-10023
SA47-LA 24/6	24.0	6.0	2.54	1.2 m	Transparent (CL), Black (BK)	30;32	301-10024
SA47-LA 32/8	32.0	8.0	2.54	1.2 m	Transparent (CL), Black (BK)	30;32	301-10025
SA47-LA 52/13	52.0	13.0	3.00	1.2 m	Transparent (CL), Black (BK)	30;32	301-10026

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools		
	30	32
	H6100	CHG900
	564	563

For more information on toolings please refer to the Application Tooling chapter.



Add items to your watchlist!

www.HT.click/9-266

