



### Non-Metallic Conduits

#### HG-DC Double Slit

Double slit corrugated conduit for retrofitting is used in control panels, machine building, plant construction.

#### Features and benefits


- Can be opened and closed repeatedly
- Cables can be inserted laterally
- Abrasion resistant
- Free of halogen, sulphur and phosphorus
- Self-extinguishing to IEC 61386
- Colour: black



HelaGuard HG-DC double slit conduit.



**To order additional HAT application tools, see page 341.**



HelaGuard non-metallic conduit

|                              |                   |
|------------------------------|-------------------|
| <b>MATERIAL</b>              | Polyamide 6 (PA6) |
| <b>Operating Temperature</b> | -40 °C to +120 °C |
| <b>Flammability</b>          | UL 94 HB          |



| TYPE    | Nominal Ø | NW Ø | Outside Ø (OD) | Inside Ø (ID) | Min. Bending Radius (R) | Weight  | Reel Length | Colour     | Article-No. |
|---------|-----------|------|----------------|---------------|-------------------------|---------|-------------|------------|-------------|
| HG-DC11 | 11        | 8.5  | 11.5           | 6.2           | 45                      | 37 g/m  | 50 m        | Black (BK) | 166-11800   |
| HG-DC13 | 13        | 10   | 12.9           | 7.9           | 55                      | 46 g/m  | 50 m        | Black (BK) | 166-11801   |
| HG-DC16 | 16        | 12   | 16.2           | 10.3          | 60                      | 72 g/m  | 50 m        | Black (BK) | 166-11802   |
| HG-DC21 | 21        | 17   | 21.0           | 13.7          | 90                      | 110 g/m | 50 m        | Black (BK) | 166-11803   |
| HG-DC28 | 28        | 23   | 28.4           | 19.8          | 105                     | 166 g/m | 50 m        | Black (BK) | 166-11804   |
| HG-DC34 | 34        | 29   | 34.2           | 26.6          | 150                     | 180 g/m | 25 m        | Black (BK) | 166-11805   |
| HG-DC42 | 42        | 36   | 43.5           | 32.3          | 170                     | 293 g/m | 25 m        | Black (BK) | 166-11806   |
| HG-DC54 | 54        | 48   | 53.3           | 44.0          | 170                     | 400 g/m | 25 m        | Black (BK) | 166-11807   |

All dimensions in mm. Subject to technical changes.

Other reel lengths available on request. Minimum Order Quantity (MOQ) may differ from package content.



**For more information on our complete HelaGuard range of conduits and fittings, please see our new HelaGuard catalogue.**



Add items to your watchlist!  
[www.HT.click/9-317](http://www.HT.click/9-317)

