



FlexiGuard conduits & fittings

PVC Conduits with steel wire spiral-reinforcement


FlexiGuard protective hoses are used to protect cables in machines and plant construction, and robotics as well as leads to switch cabinets.

Features and benefits

- Extremely flexible
- Excellent mechanical protection
- Good resistance to oils, acids and alkalis
- Good resistance to chemicals



FlexiGuard FG with FG-UH fitting.



FlexiGuard

| | |
|------------------------------|---|
| MATERIAL | Flexible Polyvinyl Chloride, cadmium free (PVC), Steel (ST) |
| Operating Temperature | -20 °C to +70 °C, (+80 °C, 200 h) |
| Flammability | UL 94 HB |



| TYPE | Nominal Ø | Inside Ø (ID) | Outside Ø (OD) | Min. Bending Radius (R) | Reel Length | Colour | Pack Cont. | Article-No. |
|------|-----------|---------------|----------------|-------------------------|-------------|-----------|------------|-------------|
| FG14 | 14 | 10 | 14 | 14 | 10 m | Grey (GY) | 10 m | 167-00209 |
| FG17 | 17 | 13 | 17 | 17 | 10 m | Grey (GY) | 10 m | 167-00211 |
| FG19 | 19 | 15 | 19 | 19 | 10 m | Grey (GY) | 10 m | 167-00213 |
| FG21 | 21 | 16 | 21 | 21 | 10 m | Grey (GY) | 10 m | 167-00216 |
| FG27 | 27 | 21 | 27 | 27 | 10 m | Grey (GY) | 10 m | 167-00221 |
| FG36 | 36 | 30 | 36 | 36 | 10 m | Grey (GY) | 10 m | 167-00229 |
| FG45 | 45 | 38 | 45 | 45 | 10 m | Grey (GY) | 10 m | 167-00236 |
| FG56 | 56 | 48 | 56 | 56 | 10 m | Grey (GY) | 10 m | 167-00248 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For more information on our complete HelaGuard range of conduits and fittings, please see our new HelaGuard catalogue.



Add items to your watchlist!
www.HT.click/9-331

