



Thermal transfer printer

TT431, Small to medium volume printing

The TT431 thermal transfer printer is perfect for printing on HellermannTyton materials such as self-adhesive labels, shrinkable tubing and identification tags. Thanks to its low weight and compact construction, the TT431 integrates seamlessly into any workstation. It is easy to use due to its intuitive colour LCD touch display and clear status messages which can be shown in multiple languages. The optional cutter and perforator make this printer ideal for a wide range of applications. 300 dpi resolution ensures that barcodes, warning symbols, logos and text are as sharp as they can be.

Features and benefits

- Small to medium volume single sided printing
- Print on HellermannTyton cable markers and labels
- Uses standard ribbons
- Barcodes: standard and 2D
- Print speed up to 150 mm/s
- Adjustable label sensor
- Multiple language selection
- Windows drivers: 32/64 Bit Windows Vista, 7, 8, 10, Windows Server 2008, 2008 R2, 2012, 2012 R2, 2016, 2019



www.HellermannTyton.com/TT431-cat22



TT431 thermal transfer printer designed for ease of operation.

Print Method	Thermal transfer printing
Print Head Type	300 dpi, flat type
Print Speed	up to 150 mm/s
Max. Print Width	105.70 mm
Label Height Max (metric)	4,000 mm
Interfaces	USB 2.0, Ethernet 10/100 Base T, RS232
Supported Barcodes, Printer	Standard and 2D
Printer Memory	256 MB RAM
Dimensions W x H x D	253 mm x 189 mm x 322 mm
Weight	4.0 kg



TYPE	Pack Cont.	Article-No.
TT431	1 pc.	556-00400

All dimensions in mm. Subject to technical changes.

TYPE	Description	Article-No.
TT430/TT431 300dpi Printhead	Printhead for TT430/TT431	556-00453
TT430/TT431 Print Roller	Print Roller for TT430/TT431	556-00454
S430 Cutter	Cutter for TT430/TT431	556-00452
P430 Perforator	Perforator for TT430/TT431	556-00456
TT External Reel Holder	External Reel Holder	556-00451

Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.



Add items to your watchlist!

www.HT.click/9-528

