Thermal transfer printer

TrakMark DS, Double Sided

The TrakMark DS is a high-performance printer for double-sided printing. This printer is perfect for double-sided printing on HellermannTyton shrinkable tubing. With two print heads mounted one on top of the other, the TrakMark DS prints onto both sides of the material at the same time. High reliability and multiple peripherals enable applications and solutions tailored to specific customer requirements. It is easy to use thanks to its display and clear status messages which can be shown in multiple languages. 300 dpi resolution ensures that barcodes, warning symbols, logos and text are as sharp as they can be.

Features and benefits

- · High volume double sided printing
- Prints perfectly on HellermannTyton heat shrink ladder style products
- Uses standard 300 m ribbons
- Barcodes: standard and 2D
- Print speed up to 125 mm/s (30 mm/s recommended for ladder style products and tubing)
- Multiple language selection
- Windows drivers: 32/64 bit for Windows XP, Windows Vista, Windows 7, 8, 10



www.HellermannTyton.com/TrakMark-cat22



TrakMark DS printer - for double sided printing.

Print Method	Thermal transfer printing	
Print Head Type	300 dpi, flat type	
Print Speed	30, 40, 50, 75, 100, 125 mm/s	
Max. Print Width	105.6 mm	
Label Height Max (metric)	2,000 mm	
Interfaces	RS232 C, USB 2.0, Ethernet 10/100 Base T	
Supported Barcodes, Printer	Standard, 2D	
Printer Memory	64 MB RAM	
Dimensions W x H x D	248 mm x 395 mm x 554 mm	
Weight	21.0 kg	



TYPE	Article-No.	
TrakMark DS	556-05000	


Subject to technical changes

ТҮРЕ	Description	Article-No.
S4000 Cutter	S4000 Cutter for TT4000 ⁺ and TrakMark DS	556-04025
P4000 Perforator	Perforator for TT4000+ and TrakMark DS	556-04024
TT External Reel Holder	External Reel Holder	556-00451

Subject to technical changes.



HellermannTyton



Date of issue: December 2021