



### Manual tensioning tool for KR-Series

#### KR6/8

Application tool KR6/8 crimps the glass-fibre-reinforced locking pin of the KR seal and leads to plastic deformation of the tie ends. This produces a very proof permanent connection.

#### Features and benefits

- Tough metal tool for applying KR cable ties only
- For tensioning, fixing and cutting KR cable ties
- Simply change the front plate to apply 6 mm or 8 mm straps



The manual tensioning tool KR6/8 for KR-Series cable ties.

TYPE	Description	For Ties	Strap Width max.	Weight	Article-No.
KR6/8	KR6/8	KR6, KR8	8.0	0.69 kg	121-00680
SP KR6/8 replacement blade	Replacement blade	KR6, KR8	-	0.002 kg	122-68019

All dimensions in mm. Subject to technical changes.

### Pneumatic tensioning tool for KR8-Series

#### KR8PNSE

Application tool KR8PNSE crimps the glass-fibre-reinforced locking pin of the KR seal and leads to plastic deformation of the tie ends. This produces a very proof permanent connection.

#### Features and benefits

- Pneumatic tool with tough metal housing
- For applying KR8 cable ties only
- For tensioning, fixing and automatic cutting KR8 cable ties
- Tension force can be adapted depending on air pressure
- Holding ring for a balancer



The pneumatic tensioning tool KR8PNSE for KR8-Series cable ties.

<b>Air Supply</b>	non oiled, oiled
<b>Air Pressure (min.)</b>	3 Bar
<b>Air Pressure (max.)</b>	4 Bar
<b>Hose Internal Diameter</b>	6.0 mm
<b>L x H x W</b>	approx. 320 x 210 x 50 mm

RoHS

TYPE	Description	For Ties	Strap Width max.	Weight	Article-No.
KR8PNSE	KR8PNSE	KR8	8.0	1.537 kg	121-00889
SP KR8PNSE replacement blade	Replacement Blade	KR8	-	0.002 kg	122-80032

All dimensions in mm. Subject to technical changes.

