



Parallel cable branch joints

RELICON PA-11 with PUR 771

The parallel branch joint PA is a universal straight-through and branch joint. Depending on the connector, it can be used for single and double branches. They are suitable for jointing on polymeric cables and wires made of PVC, XLPE, PE, EPR and utility cables.


Application: In low-voltage electrical networks as well as for signal and communication cables. For power supply lines for outdoor lighting and for cable repairs. In general connections in industrial buildings, power supply in the ground, outdoors and in the water.

Features and benefits

- One-piece, impact-proof, transparent moulding shell
- Captive lids
- Compact, optimized dimensions
- Longitudinally and transversely watertight
- Joint can be cast under influence of water
- Immediately ready for use

Content of Set / Kit

- Cast resin PUR 771
- In a two-chamber pouch
- Transparent, one-piece moulding shell
- Foam seal, protective gloves, emery cloth
- Cleaning cloth, installation instructions
- SF-nozzle (two-chamber pouch)



PA-11



Parallel branch joint PA-11 PUR 771.

MATERIAL	Polyurethane resin (PUR)
Colour	Black (BK)
Operating Temperature	-25 °C to +120 °C
Storage Temperature	+4 °C to +40 °C
Shelf Life	36 months

RoHS ✓



**Without
branch connector!**

TYPE	Ø Main Cable	Main Cable mm ² min - max		Ø Branch Cable	Branch Cable mm ² min - max		Length (L)	Height (H2)	Resin Quantity	Article-No.
PA-11 / SF	13-21	4 x 1.5	5 x 10	13-21	4 x 1.5	5 x 10	230.0	58.0	490 ml/671 g	435-00186

All dimensions in mm. Subject to technical changes.