



Cable Ties for temperatures up to + 105°C (heat stabilised)

- T-Series in PA66HS natural


These cable ties are used for routing, bundling and securing cables, pipes and hoses.

Features and Benefits

- Heat stabilised cable tie available in a wide range of sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold around bundles
- Easy application either manually or with a processing tool
- Simple to insert due to the ergonomically bent tail
- Higher temperature resistance up to +105 °C



T-Series.



T-Series

**Material specification
please see page 30.**

TYPE	Width (W)	Length (L)	Bundle Ø max.	N	Material	Colour	Pack Cont.	Article-No.
T18S	2.3	83.0	16.0	80	PA66HS	Natural (NA)	1000	111-00962
T18R	2.5	100.0	22.0	80	PA66HS	Natural (NA)	100	111-01959
	2.5	100.0	22.0	80	PA66HS	Natural (NA)	1000	111-01866
T18I	2.5	145.0	35.0	80	PA66HS	Natural (NA)	1000	111-02359
T18L	2.5	205.0	55.0	80	PA66HS	Natural (NA)	100	111-02159
	2.5	205.0	55.0	80	PA66HS	Natural (NA)	1000	111-02069
T25LL	2.8	330.0	95.0	110	PA66HS	Natural (NA)	100	111-02602
T30R	3.5	150.0	35.0	135	PA66HS	Natural (NA)	100	111-03259
T30L	3.5	198.0	50.0	135	PA66HS	Natural (NA)	100	111-03459
T30LL	3.5	290.0	80.0	135	PA66HS	Natural (NA)	100	111-01555
T40R	4.0	175.0	40.0	180	PA66HS	Natural (NA)	100	111-03859
T50S	4.6	150.0	35.0	225	PA66HS	Natural (NA)	100	111-05859
T50R	4.6	202.0	50.0	225	PA66HS	Natural (NA)	100	111-04855
T50M	4.6	245.0	65.0	225	PA66	Natural (NA)	100	111-00956
T50I	4.6	300.0	85.0	225	PA66HS	Natural (NA)	100	111-00953
T50L	4.6	390.0	110.0	225	PA66HS	Natural (NA)	100	111-05655
T80R	4.7	210.0	55.0	355	PA66HS	Natural (NA)	100	111-05059
T80I	4.7	300.0	85.0	355	PA66HS	Natural (NA)	100	111-08259
T80L	4.7	390.0	110.0	355	PA66HS	Natural (NA)	100	111-05459
T120S	7.6	225.0	55.0	535	PA66HS	Natural (NA)	50	111-12824
T120I	7.6	300.0	75.0	535	PA66HS	Natural (NA)	100	111-00959
T150R(H)	7.6	365.0	100.0	670	PA66HS	Natural (NA)	100	111-15069
T120R(E)	7.6	387.0	100.0	535	PA66HS	Natural (NA)	100	111-12059
T120XM	7.6	600.0	175.0	535	PA66HS	Natural (NA)	50	111-12719
T120L	7.6	760.0	225.0	535	PA66HS	Natural (NA)	50	111-12449

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.



For product specific approvals and specifications please refer to the Appendix.