



1-Piece Fixing Tie with Arrowhead, with Disc

- 1-Piece Fixing Tie with Arrowhead, with Disc, for round holes

With a diverse range of fixing possibilities these ties are ideal for use in many different industries, including automotive, aerospace, white goods manufacture and panel building.


Features and Benefits

- Easy to install without the need for a tool
- Arrowhead simply locks into place
- Disc adjusts tie for pressures from various directions and minimises access of dust, dirt and water
- Cable tie head always situated in a defined position
- KSFT-types with specially rounded arrowhead minimise the assembly height


Application tools
please see page 338.




The flexible disc adjusts to take up variations in panel thickness - ensuring a firm fixing at all times.




T50MD7, example of an application with metal clamp



Common head/
fixing design



T50SOSKSFT65E



T50SOSKSFT62x122PT0.7-1.3



Special design without a gap between head and bundle; T50MD7

TYPE	Width (W)	Length (L)	Bundle Ø max.	N	Disc Ø	Hole Ø (FH)	Panel Thickness	Material	Colour	Article-No.
T50SOSKSFT5.4E-MD	4.6	156.0	35.0	180	16.0	5.4	0.7 - 1.3	PA66HS	Black (BK)	126-00180
T50SOSKSFT5SE	4.6	156.0	35.0	180	16.0	4.8 - 5.2	0.7 - 1.3	PA66HS	Natural (NA)	126-00111
	4.6	156.0	35.0	180	16.0	4.8 - 5.2	0.7 - 1.3	PA66HS	Black (BK)	126-00099
T50SOSKSFT65E	4.6	156.0	35.0	180	16.0	6.3 - 6.7	0.7 - 1.3	PA66HS	Black (BK)	126-00081
T50SOSKSFT6.5S2-E	4.6	157.0	35.0	225	16.0	6.3 - 6.7	1.7 - 2.3	PA66HS	Black (BK)	126-00086
T50SOSSFT6.5E-MD	4.6	158.8	30.0	180	16	6.3 - 6.7	0.6 - 1.8	PA66HS	Green (GN)	126-00216
T50SOSSFT6.5E	4.6	158.8	30.0	200	16.0	6.3 - 6.7	1.9 - 2.5	PA66HS	Black (BK)	126-03102
T50SST5	4.6	170.0	31.0	225	16.2	6.1 - 6.5	0.7 - 1.5	PA66HS	Black (BK)	126-00017
	4.6	170.0	31.0	225	16.2	6.1 - 6.5	0.7 - 1.5	PA66	Natural (NA)	126-02300
T50SD6	5.0	160.0	31.0	225	18.0	6.3 - 7.5	0.6 - 1.8	PA66HS	Black (BK)	111-85350
T50MD7	5.0	225.0	59.0	225	16.0	6.8 - 7.2	0.8 - 2.0	PA66HS	Black (BK)	111-85850
	5.0	225.0	59.0	225	16.0	6.8 - 7.2	0.8 - 2.0	PA66	Black (BK)	126-00181
	5.0	225.0	59.0	225	16.0	6.8 - 7.2	0.8 - 2.0	PA66	Black (BK)	111-85890

All dimensions in mm. Subject to technical changes.