



### Fixing Elements for Corrugated Tubing, with Fir Tree

- CTC-Series


CTC clamps are used in the automotive, harness making and electrical industries and wherever corrugated tubing has to be quickly and firmly fixed.

#### Features and Benefits

- Available for a variety of nominal diameters
- Fir tree foot part can be used for a variety of panel thicknesses
- Suitable for use within threaded holes
- Tube is guided accurately, clipping into place
- Movement is prevented by the inside profile of the clamp



The tubing clips into the CTC clamp and is held firmly.



CTC10FT6LG

| TYPE        | Width (W) | Height (H) | Height (H2) | Nominal Ø | Disc Ø | Hole Ø (FH) | Panel Thickness | Material  | Colour     | Article-No. |
|-------------|-----------|------------|-------------|-----------|--------|-------------|-----------------|-----------|------------|-------------|
| CTC7.5FT6LG | 8.0       | 18.6       | 11.1        | 7.5       | 16.0   | 6.5 - 7.0   | 0.8 - 6.0       | PA66HIRHS | Black (BK) | 151-14313   |
| CTC7.5FT9   | 8.0       | 19.9       | 12.2        | 7.5       | 23.0   | 8.7 - 9.0   | 3.0 - 5.0       | PA66HIRHS | Black (BK) | 155-31602   |
| CTC10FT6    | 8.0       | 21.4       | 7.5         | 10.0      | 16.0   | 6.5 - 7.0   | 0.8 - 3.0       | PA66HIRHS | Black (BK) | 151-14311   |
| CTC10FT6LG  | 8.0       | 21.4       | 11.1        | 10.0      | 16.0   | 6.5 - 7.0   | 0.8 - 6.0       | PA66HIRHS | Black (BK) | 151-00018   |
| CTC10FT9    | 8.0       | 22.7       | 12.2        | 10.0      | 23.0   | 8.7 - 9.0   | 3.0 - 5.0       | PA66HIRHS | Black (BK) | 155-17801   |
| CTC13FT6    | 8.0       | 25.2       | 7.5         | 13.0      | 16.0   | 6.5 - 7.0   | 0.8 - 3.0       | PA66HIRHS | Black (BK) | 151-14312   |
| CTC13FT6LG  | 8.0       | 25.2       | 11.1        | 13.0      | 16.0   | 6.5 - 7.0   | 0.8 - 6.0       | PA66HIRHS | Black (BK) | 151-00019   |
| CTC22FT9    | 8.0       | 37.7       | 12.2        | 22.0      | 23.0   | 8.7 - 9.0   | 3.0 - 5.0       | PA66HIRHS | Black (BK) | 155-25201   |
| CTC4.5FT6LG | 10.0      | 16.1       | 11.1        | 4.5       | 16.0   | 6.5 - 7.0   | 0.8 - 6.0       | PA66HIRHS | Black (BK) | 151-14314   |
| CTCFT6      | 11.0      | 18.5       | 9.3         | 15.0      | -      | 6.3 - 6.7   | 0.7 - 4.5       | PA66HIRHS | Black (BK) | 151-00783   |

All dimensions in mm. Subject to technical changes.