



Rubber Tubing, PTFE

- FE


FE is ideal for high temperature applications, when resistance to aggressive fluids is required for example in high performance hose applications. FE tubing is also used to reduce movement due to friction, covering cable or wire.

Features and Benefits

- Thin walled rubber tubing made of PTFE
- Transparent or coloured
- Very high temperature resistance
- High abrasion resistance
- Good resistance to aggressive chemicals
- Available on reels



PTFE tubing FE.



PTFE tubing

MATERIAL	Polytetrafluoroethylene (PTFE)
Operating Temperature	-65 °C to +250 °C, intermittent +350 °C
Dielectric Strength	55 kV/mm according to IEC 60684 P2
Flammability	UL94 V0
Specifications	BS-2848 Type 6 250T, DEF STAN 59-15 Type D6

RoHS ✓

TYPE	Supplied Ø D min.	Wall (WT)	Reel Length	Colour	Article-No.
FE3	0.3	0.20	500 m	Natural (NA)	178-00005
FE4	0.4	0.25	500 m	Natural (NA)	178-00012
FE5	0.5	0.25	500 m	Natural (NA)	178-00020
FE9	0.9	0.25	500 m	Natural (NA)	178-00056
FE10	1.0	0.30	500 m	Natural (NA)	178-00068
FE11	1.1	0.30	500 m	Natural (NA)	178-00083
FE15	1.6	0.30	500 m	Natural (NA)	178-00119
FE19	1.9	0.30	250 m	Natural (NA)	178-00143

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.