



Standard polyester braided sleeving, expansion rate: 3:1

- Helagaine HEGPX

Helagaine HEGP and HEGPX braided sleeving is used in the automobile sector and in machine construction. It is also used for smaller electrical appliances to avoid pockets of high temperature. HEGP and HEGPX can be supplied in pre-cut lengths on request.

Features and Benefits

- Made of sturdy polyester
- Highly flexible
- Expansion rate of 3:1
- Easy to apply over irregular shapes
- Good abrasion resistance
- 7 sizes for diameters from 3 - 70 mm for an optimal fit

To prevent fraying, the sleeve can be cut with the hot cutting tool HSG0, see page 256.



Helagaine HEGPL Braided Sleeving.

MATERIAL	Polyester (PET)
Operating Temperature	-50 °C to +150 °C, intermittent +220 °C
Melting Point	+250 °C
Flammability	UL94 V2, FMVSS 302
Specifications	UL-Recognized

HF ✓

RoHS ✓

TYPE	Bundle Ø min.	Bundle Ø max.	Colour	Reel Length	Article-No.
HEGPX06	3.0	10.0	Black (BK)	200 m	170-00060
HEGPX09	5.0	16.0	Black (BK)	100 m	170-00090
HEGPX12	6.0	19.0	Black (BK)	100 m	170-00120
HEGPX20	13.0	32.0	Black (BK)	100 m	170-00200
HEGPX30	19.0	45.0	Black (BK)	50 m	170-00300
HEGPX40	32.0	70.0	Black (BK)	50 m	170-00400

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Cuts in any lengths. Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.