



HelaTape Wrap - Vinyl tapes

- HelaTape Wrap 25 - Vinyl tape for corrosion protection



HelaTape Wrap 25 can be used for both overhead and direct burial applications.

Features and Benefits

- Special adhesive
- Excellent protection against corrosion
- Complete environmental, mechanical and electrical protection
- Highly resistant to UV, water, oil, most chemicals, bacteria and fungus
- Used for pipes, tubes, and conduits in outside and underground applications

MATERIAL	Polyvinylchloride (PVC)
Dielectric Strength	40 kV/mm
Adhesion to Steel	2.4 N/10 mm
Adhesion to Backing	2.0 N/10 mm
Elongation at break	250 %
Breaking Strength	48 N/10 mm
Operating Temperature	+105 °C

RoHS ✓

HelaTape Shield - Conductive tapes

- HelaTape Shield 310 - Self-amalgamating, conductive tape for shielding



HelaTape Shield 310 self-amalgamating conducting tape for shielding high-voltage splices and terminations.

Features and Benefits

- Self-amalgamating shielding tape made from ethylene propylene rubber
- Electrostatic shielding for high voltage splices and terminations
- Excellent conducting properties
- Prevents corona effect
- Moisture and UV-resistant and easy to apply

MATERIAL	Ethylene Propylene Rubber (EPR)
Operating Temperature	+90 °C
Intermittent Operating Temperature	+130 °C
Water Absorption	0.02 %
Tensile Strength	2.0 MPa
Elongation at break	600 %
Volume Resistance	870 Ω cm

HF ✓

RoHS ✓

- HelaTape Wrap 25 - Vinyl tape for corrosion protection

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HTAPE-WRAP25-25x30	0.25	25.0	30.0 m	Black (BK)	710-00800
HTAPE-WRAP25-38x30	0.25	38.0	30.0 m	Black (BK)	710-00801
HTAPE-WRAP25-50x30	0.25	50.0	30.0 m	Black (BK)	710-00802
HTAPE-WRAP25-100x30	0.25	100.0	30.0 m	Black (BK)	710-00803

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

- HelaTape Shield 310 - Self-amalgamating, conductive tape for shielding

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HTAPE-SHIELD310	0.76	19.0	4.6 m	Black (BK)	711-00000
	0.76	38.0	9.1 m	Black (BK)	711-00001

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.