# Installation Devices



#### HelaTape Power - Rubber and higher voltage tapes

#### • HelaTape Power 810 - Self-amalgamating high voltage tape



HelaTape Power 810 enables jacketing splices up to 69 kV.

#### **Features and Benefits**

- Self-amalgamating tape for insulating and jacketing splices up to
- Halogen-free with outstanding corona, ozone and UV-resistance
- Void-free, electrically stable layering
- Amalgamates quickly
- Protects bus bar components
- Excellent moisture, corrosion and chemical resistance
- Ideal moisture seal for water-proofing applications

MATERIAL	Ethylene Propylene Rubber (EPR)				
<b>Operating Temperature</b>	+90 °C				
Intermittent Operating Temperature	+130 °C				
Water Absorption	0.06 %				
Tensile Strength	2.50 MPa				
Elongation at break	930 %				
Volume Resistance	$10^{1} \Omega \text{ cm}$				
Dielectric Strength	35 kV/mm				

## **RoHS**

#### HelaTape Power - Rubber and higher voltage tapes

• HelaTape Power 820 - Self-amalgamating high voltage tape,



The high-voltage tape HelaTape Power 820 yields a uniform and void-free build-up.

#### **Features and Benefits**

- Ethylene rubber-based, high-voltage, linerless, self-bonding tape
- Excellent electrical, chemical and physical properties
- Building stress cones and jacketing of terminations, bus bars and joints
- High thermal conductivity
- Quicker application due to linerless design
- Uniform and void-free layering
- Excellent stretch to conform to the most complex shapes and contours
- Flame retardent and UV resistant
- Compatible with all extruded cable insulations

MATERIAL	Ethylene Propylene Rubber (EPR)			
Operating Temperature	+90 °C			
Intermittent Operating Temperature	+130 °C			
Water Absorption	0.06 %			
Tensile Strength	3.30 MPa			
Elongation at break	900 %			
Volume Resistance	$10^{1}~\Omega$ cm			
Dielectric Strength	35 kV/mm			

### **RoHS**

#### • HelaTape Power 820 - Self-amalgamating high voltage tape, linerless

ТҮРЕ	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HTAPE-POWER810	0.76	19.0	9.1 m	Black (BK)	711-00401

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content.

#### • HelaTape Power 820 - Self-amalgamating high voltage tape, linerless

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HTAPE-POWER820	0.76	19.0	9.1 m	Black (BK)	711-00402

All dimensions in mm. Subject to technical changes

Minimum Order Quantity (MOQ) may differ from package content.

