



Heat-shrinkable wire identification, thermal transfer

- TULT - 3:1 UL-Recognized Tubing



TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Pack Cont.	Colour	Article-No.
TULT6-2BK	6.0	2.0	0.70	110 m	Black (BK)	553-40600
TULT6-2BU	6.0	2.0	0.70	110 m	Blue (BU)	553-40606
TULT6-2RD	6.0	2.0	0.70	110 m	Red (RD)	553-40602
TULT6-2WH	6.0	2.0	0.70	110 m	White (WH)	553-40609
TULT6-2YE	6.0	2.0	0.70	110 m	Yellow (YE)	553-40604
TULT9-3BK	9.0	3.0	0.80	72 m	Black (BK)	553-40900
TULT9-3BU	9.0	3.0	0.80	72 m	Blue (BU)	553-40906
TULT9-3RD	9.0	3.0	0.80	72 m	Red (RD)	553-40902
TULT9-3WH	9.0	3.0	0.80	72 m	White (WH)	553-40909
TULT9-3YE	9.0	3.0	0.80	72 m	Yellow (YE)	553-40904
TULT12-4BK	12.0	4.0	0.85	54 m	Black (BK)	553-41200
TULT12-4BU	12.0	4.0	0.85	54 m	Blue (BU)	553-41206
TULT12-4RD	12.0	4.0	0.85	54 m	Red (RD)	553-41202
TULT12-4WH	12.0	4.0	0.85	54 m	White (WH)	553-41209
TULT12-4YE	12.0	4.0	0.85	54 m	Yellow (YE)	553-41204
TULT18-6BK	18.0	6.0	1.00	26 m	Black (BK)	553-41800
TULT18-6BU	18.0	6.0	1.00	26 m	Blue (BU)	553-41806
TULT18-6RD	18.0	6.0	1.00	26 m	Red (RD)	553-41802
TULT18-6WH	18.0	6.0	1.00	26 m	White (WH)	553-41809
TULT18-6YE	18.0	6.0	1.00	26 m	Yellow (YE)	553-41804
TULT24-8BK	24.0	8.0	1.20	26 m	Black (BK)	553-42400
TULT24-8BU	24.0	8.0	1.20	26 m	Blue (BU)	553-42406
TULT24-8RD	24.0	8.0	1.20	26 m	Red (RD)	553-42402
TULT24-8WH	24.0	8.0	1.20	26 m	White (WH)	553-42409
TULT24-8YE	24.0	8.0	1.20	26 m	Yellow (YE)	553-42404
TULT39-13BK	39.0	13.0	1.25	10 m	Black (BK)	553-43900
TULT39-13BU	39.0	13.0	1.25	10 m	Blue (BU)	553-43906
TULT39-13RD	39.0	13.0	1.25	10 m	Red (RD)	553-43902
TULT39-13WH	39.0	13.0	1.25	10 m	White (WH)	553-43909
TULT39-13YE	39.0	13.0	1.25	10 m	Yellow (YE)	553-43904

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.