Electrical Hot Air Tool

• H5002 - handy tool

For applying heat shrinkable products like thin walled shrink tubing and Moulded Shapes.

Features and Benefits

- Lightweight and compact hot air tool
- Enables comfortable, fatigue-free work
- Temperature electronically controlled from 100- 600 °C, cold air step of 50 °C
- Air-flow regulation adjusted in two stages (300 l/min and 500 l/min)



H5002 - The light, convenient hot-air tool.

TYPE	Air Flow I/min	Operating Temperature	Standby Temp. °C	Wattage	Operational Voltage	Weight	Article-No.
H5002	300 - 500 l/min	+100 °C to +600 °C	50 °C	2,000 W	230 V AC ~ / 230-240 V	0.9 kg	391-50200
Z3 Reflector	-	-	-	-	-	50 g	391-50500
Z4 Wide Slot Nozzle	-	1	-	i	-	50 g	391-50600

Subject to technical changes.

Electrical Hot Air Tool

• H5004 - for professional use

H5004 electrical Hot Air Tool is designed for shrinking down many heat shrinkable products like thin wall tubing, with and without adhesive, End Caps, and Moulded Shapes.

Features and Benefits

- Professional hot air gun
- Temperature electronically controlled
- Air flow regulation
- Equiped with LED temperature indication enabeling precise temperature adjustment



H5004 - for professional use.



Accessories suitable for both H5002 and H5004.

TYPE	Air Flow I/min	Operating Temperature	Standby Temp. °C	Wattage	Operational Voltage	Weight	Article-No.
H5004	150 - 500 l/min	+50 °C to +650 °C	50 °C	2300 W	230-240V, 50Hz	1.13 kg	391-50400
Z3 Reflector	-	-	-	-	-	50 g	391-50500
Z4 Wide Slot Nozzle	-	-	-	-	-	50 g	391-50600

Subject to technical changes.

