

## Technical data sheet

Article number:  
107-00003

**Z80R**

|                              |  |
|------------------------------|--|
| Product Group                | High vibration stability and impact resistant cable ties   |
| Product Family               | Z-Series   |
| Material                     | Polyamide 6.6 (PA66)   |
| Colour                       | Natural (NA)   |
| Application Range            | Indoor Use   |
| Application Tool             | ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT |
| Bundle Diameter max (metric) | 50 mm  |
| Bundle Ø min.                | 1.5 mm   |
| Flammability                 | UL 94 V2   |
| Halogen-free                 | Yes  |
| Length (L)                   | 200 mm   |
| Min.Tensile Strength         | 355 N  |
| Operating Temperature        | -40 °C to +85 °C   |
| Package Content packed in    | bag  |
| Pack Cont.                   | 100 pcs.   |
| Releasable Closure (Yes/No)  | No   |
| Thickness (T)                | 1.3 mm   |
| Toothing (Serration)         | Inside Serrated  |
| Variant                      | Inside Serrated  |
| Weight/Unit                  | 0.0015 kg  |
| Width (W)                    | 5 mm   |

