

## Technical data sheet

**Article number:**  
**108-00028**

**X80L**

<b>Product Group</b>	Cable ties with smart design
<b>Product Family</b>	X-Series
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	MK3PNSP2, EVOcut, MK7P, MK10-SB, MK20, EVO7SP, EVO7i, EVO7ISP
<b>Bundle Ø max.</b>	110 mm
<b>Bundle Ø min.</b>	1.6 mm
<b>Flammability</b>	UL 94 HB
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	385 mm
<b>Min.Tensile Strength</b>	355 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Package Content packed in</b>	bag
<b>Pack Cont.</b>	100 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	IEC 62275, UL 62275
<b>Thickness (T)</b>	1.35 mm
<b>Toothing (Serration)</b>	Inside Serrated
<b>Variant</b>	Inside Serrated
<b>Weight/Unit</b>	0.00259 kg
<b>Width (W)</b>	4.65 mm

