


## Technical data sheet

Article number:  
111-00524

**T150R(H)**



<b>Product Group</b>	Cable Ties for higher impact resistant up to + 105°C
<b>Product Family</b>	T-Series in PA66HIRHS(S)
<b>Material</b>	Polyamide 6.6, high impact modified, heat stabilised (PA66HIRHS)
<b>Colour</b>	Black (BK)
<b>Application Tool</b>	ProCut 9 no battery, EVOcut, MK9P, MK9P w/ Upper air, MK10-SB, MK21, EVO9, EVO9SP, EVO9HT, EVO9i, EVO9iSP, EVO9iHT
<b>Bundle Ø max.</b>	100.0 mm
<b>Bundle Ø min.</b>	5 mm
<b>Flammability</b>	UL 94 HB
<b>Halogen-free</b>	Yes
<b>Length (L)</b>	365.0 mm
<b>Min.Tensile Strength</b>	670 N
<b>Operating Temperature</b>	-40 °C to +105 °C
<b>Pack Cont.</b>	100 pcs.
<b>Releasable Closure (Yes/No)</b>	No
<b>Specifications</b>	UL-ZODZ2.E85319
<b>Tooththing (Serration)</b>	Inside Serrated
<b>Variant</b>	Inside Serrated
<b>Width (W)</b>	7.6 mm

