## HellermannTyton

Technical data sheet

L   Product Group Cable Ties for higher chemical resistance and temperatures up to +170°C   Product Family T-Series in E/TFE (Tefzel®) blue   Material Ethylene Tetrafluoroethylene (E/TFE)   Colour Blue (BU)   Application Range High Temperature Environments   Bundle Ø max. 22.0 mm   Bundle Ø min. 5.0 mm   Flammability UL 94 VO   Height (H) 3.7 mm   Length (L) 100.0 mm   Min.Tensile Strength 80 N   Operating Temperature -80 °C to +170 °C   Package Content packed in pack
Product Group Cable Ties for higher chemical resistance and temperatures up to +170°C   Product Family T-Series in E/TFE (Tefzel®) blue   Material Ethylene Tetrafluoroethylene (E/TFE)   Colour Blue (BU)   Application Range High Temperature Environments   Bundle Ø max. 22.0 mm   Bundle Ø min. 5.0 mm   Flammability UL 94 V0   Height (H) 3.7 mm   Length (L) 100.0 mm   Min.Tensile Strength 80 N   Operating Temperature -80 °C to +170 °C   Package Content packed in pack
Product Family T-Series in E/TFE (Tefzel®) blue   Material Ethylene Tetrafluoroethylene (E/TFE)   Colour Blue (BU)   Application Range High Temperature Environments   Bundle Ø max. 22.0 mm   Bundle Ø min. 5.0 mm   Flammability UL 94 V0   Height (H) 3.7 mm   Length (L) 100.0 mm   Min.Tensile Strength 80 N   Operating Temperature -80 °C to +170 °C   Package Content packed in pack
Product Family T-Series in E/TFE (Tefzel®) blue   Material Ethylene Tetrafluoroethylene (E/TFE)   Colour Blue (BU)   Application Range High Temperature Environments   Bundle Ø max. 22.0 mm   Bundle Ø min. 5.0 mm   Flammability UL 94 V0   Height (H) 3.7 mm   Length (L) 100.0 mm   Min.Tensile Strength 80 N   Operating Temperature -80 °C to +170 °C   Package Content packed in pack
MaterialEthylene Tetrafluoroethylene (E/TFE)ColourBlue (BU)Application RangeHigh Temperature EnvironmentsBundle Ø max.22.0 mmBundle Ø min.5.0 mmFlammabilityUL 94 V0Height (H)3.7 mmLength (L)100.0 mmMin.Tensile Strength80 NOperating Temperature-80 °C to +170 °CPackage Content packed inpack
ColourBlue (BU)Application RangeHigh Temperature EnvironmentsBundle Ø max.22.0 mmBundle Ø min.5.0 mmFlammabilityUL 94 V0Height (H)3.7 mmLength (L)100.0 mmMin.Tensile Strength80 NOperating Temperature-80 °C to +170 °CPackage Content packed inpack
Application RangeHigh Temperature EnvironmentsBundle Ø max.22.0 mmBundle Ø min.5.0 mmFlammabilityUL 94 V0Height (H)3.7 mmLength (L)100.0 mmMin.Tensile Strength80 NOperating Temperature-80 °C to +170 °CPackage Content packed inpack
Bundle Ø max.22.0 mmBundle Ø min.5.0 mmFlammabilityUL 94 V0Height (H)3.7 mmLength (L)100.0 mmMin.Tensile Strength80 NOperating Temperature-80 °C to +170 °CPackage Content packed inpack
Bundle Ø max.22.0 mmBundle Ø min.5.0 mmFlammabilityUL 94 V0Height (H)3.7 mmLength (L)100.0 mmMin.Tensile Strength80 NOperating Temperature-80 °C to +170 °CPackage Content packed inpack
Bundle Ø min.5.0 mmFlammabilityUL 94 V0Height (H)3.7 mmLength (L)100.0 mmMin.Tensile Strength80 NOperating Temperature-80 °C to +170 °CPackage Content packed inpack
Flammability   UL 94 V0     Height (H)   3.7 mm     Length (L)   100.0 mm     Min.Tensile Strength   80 N     Operating Temperature   -80 °C to +170 °C     Package Content packed in   pack
Height (H)   3.7 mm     Length (L)   100.0 mm     Min.Tensile Strength   80 N     Operating Temperature   -80 °C to +170 °C     Package Content packed in   pack
Length (L)100.0 mmMin.Tensile Strength80 NOperating Temperature-80 °C to +170 °CPackage Content packed inpack
Min.Tensile Strength80 NOperating Temperature-80 °C to +170 °CPackage Content packed inpack
Operating Temperature-80 °C to +170 °CPackage Content packed inpack
Package Content packed in pack
Pack Cont.   100 pcs.
Releasable Closure (Yes/No) No
Specifications ANSI/UL 1565, ANSI/UL 62275
Thickness (T) 1.2 mm
Toothing (Serration) Inside Serrated
UL-File Number E64962
UV-resistant acc. to ASTM D6779 (Yes/ No)
Variant   Inside Serrated
Weight/Unit   0.00028 kg
Width (W)   2.5 mm





Technical changes and errors reserved. It's up to the customer to check the suitability for a specific application by means of tests.