

## Technical data sheet

Article number:  
111-00662

T18R



|                                    |                                   |
|------------------------------------|-----------------------------------|
| <b>Product Group</b>               | Cable ties polyamide 6.6 standard |
| <b>Product Family</b>              | T-Series in PA66 coloured         |
| <b>Material</b>                    | Polyamide 6.6 (PA66)              |
| <b>Colour</b>                      | Yellow (YE)                       |
| <b>Application Range</b>           | Indoor Use                        |
| <b>Bundle Ø max.</b>               | 22.0 mm                           |
| <b>Bundle Ø min.</b>               | 1.0 mm                            |
| <b>Flammability</b>                | UL 94 V2                          |
| <b>Halogen-free</b>                | Yes                               |
| <b>Height (H)</b>                  | 3.7 mm                            |
| <b>Length (L)</b>                  | 100.0 mm                          |
| <b>Min.Tensile Strength</b>        | 80 N                              |
| <b>Operating Temperature</b>       | -40 °C to +85 °C                  |
| <b>Package Content packed in</b>   | bag                               |
| <b>Pack Cont.</b>                  | 1000 pcs.                         |
| <b>Releasable Closure (Yes/No)</b> | No                                |
| <b>Thickness (T)</b>               | 1.1 mm                            |
| <b>Toothing (Serration)</b>        | Inside Serrated                   |
| <b>Variant</b>                     | Inside Serrated                   |
| <b>Width (W)</b>                   | 2.5 mm                            |

